



OWIEP104S TYPE




FEATURES


1. Various high power inductors are superior to be high saturation for surface mounting.

APPLICATIONS


1. Power supply for VTR, OA equipment.
2. LCD television set, notebook PC.
3. Portable communication, equipments.
4. DC/DC converters, etc.



OWIEP104S Inductance decrease by current



OWIEP104S Temperature rise by current



ELECTRICAL CHARACTERISTICS FOR OWIEP104S SERIES

Part Number	Inductance (uH) ⁽¹⁾	Test Frequency	DC Resistance (Ω MAX) ⁽²⁾	Saturation Current (A) ⁽³⁾	Temperature Current (A) ⁽⁴⁾
OWIEP104S-R22	0.22	100KHZ	2.6m	39.6	23.0
OWIEP104S-R45	0.45	100KHZ	3.7m	27.6	17.0
OWIEP104S-R80	0.8	100KHZ	5.9m	20.7	14.0
OWIEP104S-1R3	1.3	100KHZ	11.8m	16.6	10.5
OWIEP104S-1R8	1.8	100KHZ	18.6m	13.3	8.00
OWIEP104S-2R5	2.5	100KHZ	21.8m	11.8	7.40

1. Inductance tested at 0.25V. Tolerance of inductance:
0.22uH: ±30%(N) 0.45uH~2.5uH: ±20%(M)
2. DCR test temp. limits 25 °C.
3. This indicates the value of current when the inductance is 30% lower than its initial value at D.C. superposition or D.C. current.
4. To load current onto the components under normal ambient which cause the temp. change as Δt=40 °C or more lower current.
5. Please refer saturated current or the minimum temperature current as standard.